

6700 SERIES



PANEL MOUNT PRINTERS 6700 SERIES

High-speed, noiseless thermal printer incorporates the latest in thermal array printheads and microprocessor technology. Selectable functions include baud rates, fonts, print direction and black or white print.

RS232/20mA input models

6710 – 20 columns

6714 – 40 columns

RS485 input models

6750 – 20 columns

6754 – 40 columns

STANDARD FEATURES

- Excellent print quality
- 7 lines per second print speed
- High resolution – 6 dots/mm (320 dots/line)
- Printhead life – greater than 5 million lines
- Works with “clean room paper”
- Noiseless printing
- Easy paper loading
- 80 character buffer
- Selectable print character via front panel
- Selectable baud rate from 75 to 9600
- Word wrap, complete word printing
- Unique “help” command assists with setup and data entry
- Dimensions: 2.75"H x 6.31"W x 9.25"D (69.9 x 160.3 x 235.0mm)
Panel cutout: 2.68"H x 5.44"W (68 x 138mm)
- 115/230VAC operation

PROGRAMMABLE FEATURES

- Time interval¹ - establishes a specific time interval (from 1 second to 24 hours) between printing sequences
- Interval print program¹ - Implements a pre-programmed series of commands. Typical commands include time/date headers, different type size, and programmed messages
- Synchronization time¹ - Begins the interval print program at a specific time of the day
- Character program² - Allows the 6700 to communicate with non-Westcon data sources. The program establishes a sequence of up to 20 characters and executes a pre-programmed print routine after these characters have been received a designated number of times
- Printer ID² - Enables each printer to be individually addressed
- User messages² - Creates up to 64 printable messages, each up to 32 characters long
- User programs² - Defines up to 32 individual command sequences, each up to 64 characters long, which are implemented on demand using an assigned program number
- Lockout code^{1,2} - Eliminates unauthorized changes to the printer setup data

¹ Available only with Clock Option K

² Available only with 2K Buffer Option M

OPTIONS INCLUDE

- Printable real time clock
- Programmable print time interval
- Programmable messages
- Programmable print programs
- Selectable lockout code
- Selectable ID code enables printer to be individually addressed
- 2K input buffer
- Excitation power supply to power other devices